1200 W / 1000 W / 850 W / 750 W

Seasonic®

VERTEX GX



SPECIAL FEATURES

- High Efficiency, 80 PLUS® Gold Certified
- Fully Modular
- ATX 3.1 and 16-Pin PCIe Gen 5.1 Cable (12V-2x6)
- Top-Quality 135 mm Fluid Dynamic Bearing Fan
- Premium Hybrid Fan Control
- Tight Voltage Regulation (12 V, 5 V and 3.3 V) [± 3 %]
- Gold Plated High Current Terminal (MB, CPU and PCIe)
- 12 Years Warranty

80 PLUS GOLD

ATX 3.1 | PCIe 5.1 READY

RTX 50 READY Seasonic

POWER DISTRIBUTION

Model	+3.3 V	+5 V	+12 V	-12 V	+5 Vsb	Total Power
VERTEX GX-1200	25 A	25 A	100 A	0.3 A	3 A	1200 W
	125 W		1200 W	3.6 W	15 W	
VERTEX GX-1000	25 A	25 A	83 A	0.3 A	3 A	1000 W
	125 W		996 W	3.6 W	15 W	
VERTEX GX-850	25 A	25 A	70 A	0.3 A	3 A	850 W
	100 W		840 W	3.6 W	15 W	
VERTEX GX-750	20 A	20 A	62 A	0.3 A	3 A	750 W
	100 W		744 W	3.6 W	15 W	

CONNECTOR QUANTITY

Cable / Model	Main Power (24P / 20P) 610 mm	EPS 12 V / ATX 12 V (8P / 4P) 700 mm	12V-2x6 (12+4 Pins) 700 mm	PCI-E (8P / 6P) 750 mm	SATA 950 mm	SATA 3.3 550 mm	Peripheral (4P) 690 mm
VERTEX GX-1200	1	2	1	3	16	2	3
VERTEX GX-1000	1	2	1	3	16	2	3
VERTEX GX-850	1	2	1	3	16	2	3
VERTEX GX-750	1	2	1	2	12	2	3

CYBENETICS PLATINUM

CYBENETICS GOLD

CYBENETICS A

CYBENETICS A-

For more information on Cybenetics certifications please visit: www.cybenetics.com.

12 YEARS WARRANTY

Compliance: TÜV CB FC R33080 EAC ErP 2013 compliant Lot 6

Protection Features: OPP / OVP / UVP / SCP / OCP / OTP

Dimensions: 170 mm (L) x 150 mm (W) x 86 mm (H)

Specifications may change without prior notice

Seasonic®

Headquarters sales@seasonic.com
USA ssa.sales@seasonic.com
Europe sse.sales@seasonic.com

www.seasonic.com